

Technical drawing of a cable gland assembly. The drawing includes a side view and a detail view of the mounting plate.

Dimensions:

- Top flange width: 115
- Top flange hole spacing: 103 (center-to-center), 50 (edge-to-center)
- Side view height: 115
- Side view width: 95
- Mounting plate diameter: $\phi 200$, $\phi 254$, $\phi 300$
- Mounting plate hole spacing: 200 (center-to-center), 5 (edge-to-center)
- Mounting plate hole size: M16
- Bottom flange diameter: $\phi 72$
- Bottom flange height: 75
- Bottom flange width: 155
- Total height: 323

Detail View:

The detail view shows the mounting plate with four M16 holes. The hole spacing is 200 (center-to-center) and 5 (edge-to-center). The plate has three concentric circles with diameters $\phi 200$, $\phi 254$, and $\phi 300$.

Notes:

- 1) Gewinde für Kabel gemäß Auftragsbe techn. Datenblatt

Für alle übrigen Maße der Stellantriebe/Getriebe siehe Maßblatt neuester Ausgabe
For all other dimensions of actuators/gear boxes refer to latest issue of dimension sheet

-
- Technical drawing of a mechanical component, showing a side view and a top view. The side view dimensions are: 161, 122, 191, 63, 115, 121, 210, 200, 20, 420, 920. The top view dimensions are: 330, 165, 160, 115. The drawing includes a central circular feature with a triangular cutout and a small rectangular feature on the right side.

Art.-Nr.				Allgemeintoleranz ISO 2768 - mK		Maßstab	
						1:5	
				Datum		Name	
				Bearb. 2011-09-27		Altmann	
				Gepr. 2011-09-28		Emenegger	
				Freig. 2011-09-28		Altmann	
				AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/809-0 Fax 07631/13218			
Zust.		Änderung		Datum		Name	

latt-	
lr. 1	
nz. 1	