

Technical drawing of a mechanical component, showing a side view and a top view. The drawing includes the following dimensions:

- Side View Dimensions:**
 - Overall width: 1045
 - Overall height: 337
 - Top flange width: 220
 - Top flange height: 115
 - Top flange outer diameter: $\phi 101$
 - Top flange inner diameter: $\phi 160$
 - Top flange thickness: 20
 - Top flange hole diameter: $\phi 20$
 - Top flange hole spacing: 148
 - Top flange hole diameter: $\phi 116$
 - Top flange hole spacing: 171
 - Top flange hole diameter: $\phi 187$
 - Top flange hole spacing: 63
 - Top flange hole diameter: $\phi 232$
 - Top flange hole spacing: 418
- Top View Dimensions:**
 - Overall width: 428
 - Overall height: 410
 - Top flange width: 300
 - Top flange height: 160
 - Top flange outer diameter: $\phi 26$ H8
 - Top flange inner diameter: $\phi 115$
 - Top flange thickness: 30 h11
 - Top flange hole diameter: $\phi 115$
 - Top flange hole spacing: 160
 - Top flange hole diameter: $\phi 175$
 - Top flange hole spacing: 240
 - Top flange hole diameter: $\phi 400$
 - Top flange hole spacing: 428
- Other Dimensions:**
 - Top flange hole diameter: $\phi 26$ H8
 - Top flange hole spacing: 30 h11
 - Top flange hole diameter: $\phi 115$
 - Top flange hole spacing: 160
 - Top flange hole diameter: $\phi 175$
 - Top flange hole spacing: 240
 - Top flange hole diameter: $\phi 400$
 - Top flange hole spacing: 428

Für alle übrigen Maße der Stellantriebe/Getriebe siehe Maßblatt neuester Ausgabe
For all other dimensions of actuators/gear boxes refer to latest issue of dimension sheet

Art.- Nr.				Allgemeintoleranz ISO 2768 - mK		Maßstab		auma® AUMA Riester GmbH & Co. KG						
						1:6		SA(R)07-AM-GF160.3 -GZ160.3-LL-LR						
					Datum	Name	U3.2753					Blatt- Nr. 1 Anz. 1		
				Bearb.	05.02.2007	Duffner								
				Gepr.	12.02.2007	Gerbig								
					Norm.		AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/809-0 Fax 07631/13218							
Zust.	Änderung	Datum	Name											