

Technical drawing of AUMA actuators showing various views and dimensions for versions SH, SB, SE, S, and thermal overload relay.

Dimensions (mm):

- Version SH: 245, 115, 115
- Version SB: 270, 115, 115
- Version SE: 282, 150, 115
- Version S: 220, 115, 115, 119, 67, 90, 75, 100, 106, 128, 130, 414, 300, 254, 160, 200, 16, 8, 16, 158, 231, 242, 245, 14.2, 14.6, 316, 241, 331, 832, 340, 173, 265, 150, 150, 94, 25, 315, 400
- Version with thermal overload relay: 349, 155, 84, 340, 173, 265, 150, 150, 94, 25, 315, 400

Output drive A: M16, F25, G4, 200, 160, 254, 300

1) Thread for cable entries acc. to order acknowledgement or technical data sheet

*also valid for: SA14.6

Art.-Nr.	Allgemeintoleranz ISO 2768 - mK	Maßstab
	1:5	
	Datum	Name
	Bearb. 2024-08-06	Goltsev
	Gepr. 2024-08-07	Demir
	Freig. 2024-08-07	Goltsev
	AUMA Riester GmbH & Co. KG P.O. Box 1362 79373 Muelheim/Germany Tel. +49 7631 809-0 Fax +49 7631 13218	
02	2449/2024	2024-08-06
01	735/2015	2015-10-19
Zust.	Änderung	Datum

auma® AUMA Riester GmbH & Co. KG	
SA(R)14.2-AC2-GK25.2	
U2.3552	
* - SA14.6	

Blatt-Nr.	Anz.
1	1

For all other dimensions of actuators/gearboxes, refer to the latest dimension sheet issue

*also valid for: SA14.6

Art.-Nr.					Allgemeintoleranz ISO 2768 - mK		Maßstab 1:5		auma® AUMA Riestler GmbH & Co. KG		
									SA(R)14.2-AC2-GK25.2		
					Datum		Name				
					Bearb. 2024-08-06		Goltsev				
					Gepr. 2024-08-07		Demir				
					Freig. 2024-08-07		Goltsev		U2.3552		
					AUMA Riestler GmbH & Co. KG						
					P.O. Box 1362						
					79373 Muelheim/Germany						
02	2449/2024	2024-08-06	Gal		Tel. +49 7631 809-0				Blatt-Nr. 1		
01	735/2015	2015-10-19	Gal		Fax +49 7631 13218				Anz. 1		
Zust.	Änderung	Datum	Name								
										* - SA14.6	