

Technical drawing showing dimensions for various versions of a device (likely a motor or actuator) and its mounting options.

Version SH

Dimensions: 245, 115, 115

Version SB

Dimensions: 270, 115, 115

Version SE

Dimensions: 282, 150, 115

Version S

Dimensions: 220, 103, 75, 40, 115, 95, 201, 344, 106, 5, 260, 356, 415, M30x47

Version with thermal overload relay

Dimensions: 155, 84, 349

Plane flange option

Dimensions: 106, 356, 415, M30x47

Main Assembly Dimensions:

Top view: 265, 173, 150, 148, 116, 186, 63, 20, 225, 300, 352, 860, 101, 160, 169, 168, 236, 100, 350

***also valid for: SA07.6**

Mounting position A

All dimensions in mm

For all other dimensions of actuators/gearboxes, refer to the latest dimension sheet issue

AUMA Riestler GmbH & Co. KG

SA(R)07.2-AC2
-GQB160.1-F35-RR-RL

U2.7061

Page 1
Qty 1

* - SA07.6 - 563:1 / 880:1 / 1784:1

1) Thread for cable entries acc.
to order acknowledgement
or technical data sheet

						Scale		 AUMA Riester GmbH & Co. KG		
						1:5				
				Date	Name	SA(R)07.2-AC2 -GQB160.1-F35-RR-RL				
				Edited	2022-01-10					Goltsev
				Checked	2022-01-14					Demir
				Rel.	2022-01-14	Goltsev				
				AUMA Riester GmbH & Co. KG P.O. Box 1362 79733 Muelheim/Germany Tel. +49 7631 809-0 Fax +49 7631 13218			U2.7061		Page 1	
									Qty 1	
State		Revision		Date		Name		*- SA07.6 - 563:1 / 880:1 / 1784:1		