

Version SH

245

115

1)

Version SB

270

115

1)

Version SE

282

150

1)

Technical drawing of the 3000 Series 3-Port Valve, Version S. The drawing includes three views: a front view (top left), a side view (top right), and a top view (bottom). Dimensions are provided in millimeters.

Front View (Top Left):

- Overall width: 220
- Overall height: 115
- Distance from centerline to top edge: 103
- Distance from centerline to side edge: 75
- Distance from centerline to bottom edge: 40

Side View (Top Right):

- Overall width: 349
- Distance from centerline to side edge: 155
- Distance from centerline to bottom edge: 84

Top View (Bottom):

- Overall width: 295
- Overall height: 118
- Distance from centerline to side edge: 95
- Distance from centerline to bottom edge: 57
- Distance from centerline to top edge: 115
- Distance from centerline to side edge (to mounting hole): 140
- Distance from centerline to side edge (to mounting hole): 175
- Distance from centerline to side edge (to mounting hole): 115
- Distance from centerline to side edge (to mounting hole): 5
- Distance from centerline to side edge (to mounting hole): $\phi 38$
- Mounting hole size: M16x25

Technical drawing of a mechanical part showing dimensions: 57, 3,5, 92, and 100.

*gilt auch für: SA07.6
Montage Position A

							Maßstab		auma® AUMA Riester GmbH & Co. KG						
							1:5		SA(R)07.2-AC2 -GS80.3-F14-RR-RL						
						Datum	Name								
					Bearb.	2022-02-18	Goltsev								
					Gepr.	2022-02-24	Demir								
					Freig.	2022-02-24	Goltsev			U2.3625					
					AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/609-0 Fax 07631/13218										
	01	0099/2022	2022-02-18	Gol								Blatt 1			
	Zust.	Änderung	Datum	Name								Anz. 1			
* - SA07.6 - 53:1 / 82:1															

Für alle übrigen Maße der Stellantriebe/Getriebe
siehe Maßblatt neuester Ausgabe