

Technical drawing of a mechanical component, likely a pump or motor housing, showing front and side views with dimensions.

Front View Dimensions:

- Overall width: 517
- Distance from left edge to centerline: 103
- Distance from centerline to right edge: 231
- Top flange width: 115
- Top flange height: 115
- Top flange mounting holes: 4 (2 on each side of centerline)
- Top flange mounting hole diameter: $\varnothing 11$
- Top flange mounting hole pitch: 119 (between first two holes on each side), 67 (between second and third holes on each side), 90 (between third and fourth holes on each side)
- Top flange mounting hole offset: 100 (from centerline to first hole on each side)
- Top flange mounting hole diameter: $\varnothing 11$
- Top flange mounting hole pitch: 119 (between first two holes on each side), 67 (between second and third holes on each side), 90 (between third and fourth holes on each side)
- Top flange mounting hole offset: 100 (from centerline to first hole on each side)

Side View Dimensions:

- Overall height: 415
- Distance from top flange to bottom flange: 260
- Bottom flange diameter: $\varnothing 356$
- Bottom flange thickness: 5
- Bottom flange mounting holes: 4 (2 on each side of centerline)
- Bottom flange mounting hole diameter: M30
- Bottom flange mounting hole pitch: 119 (between first two holes on each side), 67 (between second and third holes on each side), 90 (between third and fourth holes on each side)
- Bottom flange mounting hole offset: 100 (from centerline to first hole on each side)

Technical drawing of a mechanical component, likely a valve or fitting, showing a top view and a side view. The top view is a hexagonal shape with a central circular hole and a smaller hexagonal hole. The side view shows a cylindrical body with a flange and a mounting bracket. Dimensions are provided in millimeters.

Key dimensions and features:

- Top View:
 - Overall width: 450
 - Central circular hole diameter: $\varnothing 315$
 - Inner hexagonal hole: $\varnothing 400$
- Side View:
 - Overall height: 576
 - Top flange diameter: $\varnothing 153$
 - Top flange thickness: 115
 - Top flange width: 231
 - Top flange height: 158
 - Top flange width: 242 SA 14.2
 - Top flange height: 245 SA 14.6
 - Top flange width: 8
 - Top flange height: 16
 - Top flange width: 94
 - Top flange height: $\varnothing 25$
 - Top flange width: SA 14.2
 - Top flange height: SA 14.6
 - Top flange width: 226

Art.-Nr.					Allgemeintoleranz ISO 2768 - mK		Maßstab		 AUMA Riester GmbH & Co. KG				
Nr.							1:5						
						Datum	Name		SA(R)14.2-GK35.2				
					Bearb.	2012-08-24	Duffner						
					Gepr.	2012-08-28	Altmann						
					Freig.	2012-08-28	Duffner						
					AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/809-0 Fax 07631/13218						U2.3832		Blatt- Nr. 1 Anz. 1
	Zust.	Änderung	Datum	Name	gilt auch für/also valid for SA14.6								