

Technical drawing of a mechanical component, likely a pump or motor, showing front and side views with dimensions.

Front View Dimensions:

- Overall width: 376
- Distance from left edge to centerline: 115
- Distance from centerline to right edge: 90
- Distance from top edge to centerline: 119
- Distance from centerline to bottom edge: 67
- Distance from left edge to centerline (lower section): 100
- Distance from centerline to right edge (lower section): 90
- Distance from bottom edge to centerline (lower section): 170
- Distance from centerline to right edge (lower section): 5
- Distance from bottom edge to centerline (lower section): 90
- Distance from centerline to right edge (lower section): 170
- Distance from bottom edge to centerline (lower section): 376

Side View Dimensions:

- Overall height: 350
- Distance from top edge to centerline: 230
- Distance from centerline to bottom edge: 298
- Distance from bottom edge to centerline: 350
- Distance from centerline to right edge: 230
- Distance from centerline to right edge: 298
- Distance from centerline to right edge: 350

Other Details:

- Four M20 mounting holes are shown in the side view.
- A central shaft or rod is visible in the front view.
- A small detail '1)' points to a feature on the top left of the front view.

Technical drawing of a mechanical component, showing front and top views with dimensions.

Front View Dimensions:

- Overall width: 115
- Overall height: 946
- Top flange diameter: $\varnothing 153$
- Top flange thickness: 231
- Top flange inner diameter: 158
- Top flange outer diameter: 242 SA 14.2
- Top flange inner diameter: 245 SA 14.6
- Top flange thickness: 8
- Top flange inner diameter: 16
- Top flange outer diameter: $\varnothing 25$
- Top flange thickness: 94
- Top flange inner diameter: $\varnothing 315$
- Top flange outer diameter: $\varnothing 400$
- Top flange thickness: 226
- Top flange inner diameter: 430
- Top flange outer diameter: 946

Top View Dimensions:

- Overall width: 160
- Overall height: 165
- Top flange width: 115
- Top flange height: 350
- Top flange width: 160
- Top flange height: 165

- | | | | | | | | | | | | |
|----------|-------|----------|-------|--|------------|---------|--|---|-------------------------------------|-----------------------|--|
| Art.-Nr. | | | | Allgemeintoleranz
ISO 2768 - mK | | Maßstab | | 
AUMA Riesler GmbH & Co. KG | | | |
| | | | |  | | 1:5 | | | | | |
| | | | | | Datum | Name | | SA(R)14.2-GS160.3-F30
-GZ160.3-LL-LR | | | |
| | | | | Bearb. | 2013-08-23 | Goltsev | | | | | |
| | | | | Gepr. | 2013-08-26 | Duffner | | | | | |
| | | | | Freig. | 2013-08-26 | Goltsev | | | | | |
| | | | | AUMA Riesler GmbH & Co. KG
Postfach 1362
D-79373 Müllheim
Tel. 07631/809-0
Fax 07631/13218 | | | | U2.4121 | | Blatt-Nr. 1
Anz. 1 | |
| | Zust. | Änderung | Datum | Name | | | | | gilt für/valid for SA14.6 - 4:1/8:1 | | |