

A
—
B
—
C
—
D
—
E
—
F
—
G

Standard version KP

Technical drawing showing the standard version KP of a mechanical component. The drawing includes front, top, and side views with the following dimensions:

- Front View Dimensions:**
 - Overall width: 428
 - Overall height: 1101
 - Top flange width: 292
 - Top flange height: 189
 - Top flange inner width: 154
 - Top flange inner height: 154
 - Top flange outer height: 115
 - Top flange outer width: 154
 - Top flange inner diameter: $\phi 25$
 - Top flange outer diameter: $\phi 315$
 - Top flange thickness: 94
 - Top flange hole diameter: $\phi 25$
 - Top flange hole position: SA 14.2, SA 14.6
 - Top flange hole diameter: $\phi 315$
 - Top flange hole position: $\phi 400$
 - Top flange hole diameter: 242 SA 14.2, 245 SA 14.6
 - Top flange hole position: 8, 16
 - Top flange hole diameter: 231
 - Top flange hole position: 158
 - Top flange hole diameter: 240
 - Top flange hole position: 175
 - Top flange hole diameter: 300
 - Top flange hole position: 160
 - Top flange hole diameter: 400
 - Top flange hole position: 428
- Top View Dimensions:**
 - Overall width: 428
 - Overall height: 1101
 - Top flange width: 292
 - Top flange height: 189
 - Top flange inner width: 154
 - Top flange inner height: 154
 - Top flange outer height: 115
 - Top flange outer width: 154
 - Top flange inner diameter: $\phi 25$
 - Top flange outer diameter: $\phi 315$
 - Top flange thickness: 94
 - Top flange hole diameter: $\phi 25$
 - Top flange hole position: SA 14.2, SA 14.6
 - Top flange hole diameter: $\phi 315$
 - Top flange hole position: $\phi 400$
 - Top flange hole diameter: 242 SA 14.2, 245 SA 14.6
 - Top flange hole position: 8, 16
 - Top flange hole diameter: 231
 - Top flange hole position: 158
 - Top flange hole diameter: 240
 - Top flange hole position: 175
 - Top flange hole diameter: 300
 - Top flange hole position: 160
 - Top flange hole diameter: 400
 - Top flange hole position: 428
- Side View Dimensions:**
 - Overall width: 428
 - Overall height: 1101
 - Top flange width: 292
 - Top flange height: 189
 - Top flange inner width: 154
 - Top flange inner height: 154
 - Top flange outer height: 115
 - Top flange outer width: 154
 - Top flange inner diameter: $\phi 25$
 - Top flange outer diameter: $\phi 315$
 - Top flange thickness: 94
 - Top flange hole diameter: $\phi 25$
 - Top flange hole position: SA 14.2, SA 14.6
 - Top flange hole diameter: $\phi 315$
 - Top flange hole position: $\phi 400$
 - Top flange hole diameter: 242 SA 14.2, 245 SA 14.6
 - Top flange hole position: 8, 16
 - Top flange hole diameter: 231
 - Top flange hole position: 158
 - Top flange hole diameter: 240
 - Top flange hole position: 175
 - Top flange hole diameter: 300
 - Top flange hole position: 160
 - Top flange hole diameter: 400
 - Top flange hole position: 428

Version KPH

317

115

1)

Version KES

429

150

1)

For all other dimensions of actuators/gearboxes,
refer to the latest dimension sheet issue

1) Thread for cable entries acc.
to order acknowledgement
or technical data sheet

						Scale 1:5		auma® AUMA Riestler GmbH & Co. KG			
								SA(R)Ex14.2-AM -GF160.3-RR-RL			
						Date		Name			
				Edited 2019-01-25		Goltsev		U2.4355			
				Checked 2019-02-08		Duffner					
				Rel. 2019-02-11		Goltsev					
				AUMA Riestler GmbH & Co. KG P.O. Box 1362 79373 Muelheim/Germany Tel. +49 7631 809-0 Fax +49 7631 13218						Page 1	
										Qty 1	
01	032/2019	2019-01-25	Gol								
State	Revision	Date	Name								
* - SAE14.6 - 54:1											