


Technical drawing of a mechanical component, likely a pump or motor, showing front and side views with dimensions.

Front View Dimensions:

- Overall width: 383
- Top flange width: 115
- Top flange mounting holes: 4 (2 on each side of the centerline)
- Top flange thickness: 11
- Top flange to centerline distance: 119
- Top flange to main body distance: 67
- Top flange to bottom flange distance: 90
- Main body width: 107
- Main body height: 115
- Main body to bottom flange distance: 170
- Bottom flange diameter: $\varnothing 72$
- Bottom flange thickness: 5

Side View Dimensions:

- Overall height: 350
- Internal diameter: $\varnothing 298$
- Internal diameter: $\varnothing 230$
- Internal diameter: M20

[illegible]

Technical drawing showing the front view of a 1000 Series 1/2" component. The drawing includes dimensions: a width of 115 and a height of 282. A callout '1)' points to the top flange area, which features four circular holes arranged in a 2x2 grid.

Art.-Nr.				Allgemeintoleranz ISO 2768 - mK		Maßstab 1:5		 AUMA Riester GmbH & Co. KG	
						Datum		Name	
				Bearb.		2015-10-21		Goltsev	
				Gepr.		2015-10-22		Duffner	
				Freig.		2015-10-22		Goltsev	
				AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/809-0 Fax 07631/13218					
				SA(R)Ex14.2-GS160.3 -F30-Version LL-LR					
				U2.4825					
				gilt auch für/also valid for SA14.6 - 54:1					
Zust.	Änderung	Datum	Name	Blatt-Nr. 1 Anz. 1					