

Technical drawing of a mechanical component, likely a pump or motor housing, showing front and side views with dimensions.

Front View Dimensions:

- Overall width: 311
- Overall height: 690
- Top flange width: 128
- Top flange height: 150
- Top flange offset: 100
- Top flange radius: 170
- Top flange thickness: 102
- Top flange hole diameter: $\varnothing 300$
- Top flange hole pitch diameter: $\varnothing 406$
- Top flange hole outer diameter: $\varnothing 475$
- Top flange hole thread: M36
- Top flange hole offset: 247
- Top flange hole thickness: 5

Side View Dimensions:

- Overall width: 411
- Overall height: 690
- Top flange width: 128
- Top flange height: 150
- Top flange offset: 100
- Top flange radius: 170
- Top flange thickness: 102
- Top flange hole diameter: $\varnothing 300$
- Top flange hole pitch diameter: $\varnothing 406$
- Top flange hole outer diameter: $\varnothing 475$
- Top flange hole thread: M36
- Top flange hole offset: 247
- Top flange hole thickness: 5

1) Gewinde für Kabeleinführungen
gemäß Auftragsbestätigung
*Threads for cable entries
according to order acknowledgement*

Für alle übrigen Maße der Stellantriebe/Getriebe siehe Maßblatt neuester Ausgabe
For all other dimensions of actuators/gear boxes refer to latest issue of dimension sheet

Art.-Nr.					Allgemeintoleranz ISO 2768 - mK		Maßstab		auma® AUMA Riester GmbH & Co. KG								
							1:7										
						Datum	Name		SA(R)25.1-GK40.2								
					Bearb.	20.01.1992	Duffner										
					Gepr.	20.01.1992	Gerbig										
					Norm.												
					AUMA Riester GmbH & Co. KG Postfach 1362 D-79373 Müllheim Tel. 07631/809-0 Fax 07631/13218							U3.1124			Blatt-Nr.		1
	02	210/2006	03.05.2006	Du													
	01	Rev.1	09.11.2004	Wal													
	Zust.	Änderung	Datum	Name								auma norm					